(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 23 August 2001 (23.08.2001)

PCT

(10) International Publication Number WO 01/61769 A2

(51) International Patent Classification7:

(21) International Application Number: PCT/RO01/00004

(22) International Filing Date: 15 February 2001 (15.02.2001)

(25) Filing Language:

English

H01M 2/00

(26) Publication Language:

English

(30) Priority Data:

a 2000 00181

18 February 2000 (18.02.2000) RO

(71) Applicant and

(72) Inventor: STAVAR, Iordan [RO/RO]; Calea Giulesti nr., 44-7-c-4, ap. 87, R-77793 Bucuresti (RO). ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published:

--- without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE,

(54) Title: BOX FOR AUTOMOBILE ACCUMULATORS



(57) Abstract: The invention is about a box for automobile accumulator batteries that function in the surroundings at extreme temperatures, ranging from -30 °C to +90 °C. According to this invention, the box consists of two frameworks (1, 2), one superposed upon the other, between which there is a space (a) filled with a thermo-insulating layer made of polyurethane foam. Made up of two plane elements (3, 4), between which the polyurethane foam is introduced, the lid (B) has several holes (b) in which filler caps are screwed up (6). The invention proves useful due to the following advantages: it eliminates the thermal shocks of the automobile accumulators - the thermal shocks of which significantly reduce their safety during exploitation; it eliminates the frequent recharging during the wintertime; it gives easiness of exploitation.

) 01/61769 A

PCT/RO01/00004 .

BOX FOR AUTOMOBILE ACCUMULATORS

The invention is used by the accumulator-manufacturing industry, in the production of electric generators for the starting and running supply for road, railroad, sea and air means of transportation.

Automobile accumulators are well known, being set up in the engine compartment as a rule, where they have to resist external temperatures ranging from -30° C to $+90^{\circ}$ C.

These high temperature variations, and especially the low temperatures, worsen the starting efficiency.

Since the number of trials to start the automobiles during the freezing season increases, the period of actual exploitation of the accumulator decreases.

The technical problem that this invention solves resides in the thermal insulation and maintenance of constant temperature inside the battery, as constant as possible, through the appropriate construction of the box.

The invention enables the box to fight the disadvantages of slow start, low efficiency and reduced exploitation of the accumulator through its particular construction: the box consists of two frameworks, one being superposed upon the other, between which an inner space forms, which is filled with a thermal-insulating material.

I have put the invention into practice by realizing the accumulator, which turned out to have excellent results.

By applying this invention, the following advantages are obtained:

- the functioning duration of accumulators is lengthened from 3-4 years to 7-9 years;

WO 01/61769 PCT/RO01/00004

- a relatively constant temperature of the accumulator is maintained, which protects it against the high temperature differences in both the winter and the summer;

- the accumulators are exploited easily during the frosty weather of the winter;
 - the weight of the accumulators is low;
- the environment is protected against the pollutants resulted in the manufacturing process of lead, through the extension of the accumulator functioning period.

Here is an example of realization in connection, and the additional figures representing:

FIG. 1. - Longitudinal section through the framework.

FIG. 2. - Section through the plug.

According to the invention, the box A consists of an inner framework 1 made of a known plastic material, resistant to acid, and an outer framework 2 made of the same material plastic or a different one, less resistant to acid (FIG.1).

Between the two frameworks there is a space filled with thermal-insulating foam.

The procedure of filling with thermal-insulating foam is a known one, and it can be carried out either manually, using the doses of polyurethane foam on the market, or industrially, the component 1 and 2 of the box, as well as the components 3 and 4 of the lid B have orifices for filling up, and orifices for overflowing, which do not show in the picture.

The lid B also consists of two elements, the frameworks 3 and 4, between which the space a is situated, having the same width and containing the same insulating layer of 7-10 mm width.

." .

3

WO 01/61769 PCT/RO01/00004

The lid B has a series of holes b, in which several plugs 6 are screwed up, and a series of holes c, through which the electrodes of the battery come out.

The body A has a rigidity 5 in each of the four inferior corners.

The plugs 6 are made of the same plastic material as the one of the inner body 1 of the box A.

They are filled with the same thermal-insulating material.

The plugs 6 have each a canal d connecting the inside of the battery with the exterior, keeping them at atmospheric pressure, while the canals d open into a cavity e situated on top of the plug.

The cavity **e** is connected to the atmosphere through an orifice **f** situated eccentrically in comparison with the canal **d** in order to avoid the penetration of dust or other obturating particles.

The accumulator observes DIN, SAE, and EN norms through the modification of the moulds for the grills.

. WO 01/61769 PCT/RO01/00004

INVENTION SUMMARY OF THE BOX FOR AUTOMOBILE ACCUMULATORS


The invention is about a box for automobile accumulator batteries that function in the surroundings at extreme temperatures, ranging from -30°C to +90°C. According to this invention, the box consists of two frameworks (1, 2), one superposed upon the other, between which there is a space (a) filled with a thermo-insulating layer made of polyurethane foam. Made up of two plane elements (3, 4), between which the polyurethane foam is introduced, the lid (B) has several holes (b) in which filler caps are screwed up (6). The invention proves useful due to the following advantages: it eliminates the thermal shocks of the automobile accumulators — the thermal shocks of which significantly reduce their safety during exploitation; it eliminates the frequent recharging during the wintertime; it gives easiness of exploitation.


WO 01/61769 PCT/RO01/00004

REVENDICATIONS

the fact that it is made up of a framework A consisting of two superposed bodies 1 and 2, between which there is a space (a) which is filled up with a thermal-insulating layer made of polyurethane foam, a lid B consisting of two plane elements (3, 4) between which the same foam is introduced and having several holes (b), in which the filler caps 6 are screwed up, and several holes (c) through which the clamps of the accumulator come out, the framework A and the lid B being hermatically attached to one another through thermal fusing.

R2 Filler cap, in concordance with revendication 1, characterized by the fact that it is filled with the same polyurethane foam, offering the space (e) for protection against dust or rough elements that may obturate the canal (d), having an orifice (f) eccentrically situated in comparison with the axis of the canal (d).





THIS PAGE BLANK (USPTO)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date 23 August 2001 (23.08.2001)

PCT

(10) International Publication Number WO 01/61769 A3

(51) International Patent Classification⁷: 2/02, 2/12, 2/04

H01M 2/10.

KG. KP. KR. KZ. LC. LK. LR. LS. LT. LU. LV. MD. MG. MK. MN. MW. MX. NO. NZ. PL. PT. RO. RU. SD. SE. SG. SI. SK. SL. TJ. TM. TR. TT. UA. UG. US. UZ. VN. YU. ZA. ZW.

patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,

CG. Cl. CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

(21) International Application Number: PCT/RO01/00004

(22) International Filing Date: 15 February 2001 (15.02.2001)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

a 2000 00181

18 February 2000 (18.02.2000) RO

Published:

--- with international search report

(71) Applicant and

(72) Inventor: STAVAR, Iordan [RO/RO]: Calea Giulesti nr., 44-7-c-4, ap. 87, R-77793 Bucuresti (RO).

(88) Date of publication of the international search report: 21 February 2002

____,

(81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, JP, KE,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Guzette.

= (

A

(54) Title: BOX FOR AUTOMOBILE ACCUMULATORS

(57) Abstract: The invention is about a box for automobile accumulator batteries that function in the surroundings at extreme temperatures, ranging from -30 °C to +90 °C. According to this invention, the box consists of two frameworks (1, 2), one superposed upon the other, between which there is a space (a) filled with a thermo-insulating layer made of polyurethane foam. Made up of two plane elements (3, 4), between which the polyurethane foam is introduced, the lid (B) has several holes (b) in which filler caps are screwed up (6). The invention proves useful due to the following advantages: it eliminates the thermal shocks of the automobile accumulators - the thermal shocks of which significantly reduce their safety during exploitation; it eliminates the frequent recharging during the wintertime; it gives easiness of exploitation.

INTERNATIONAL SEARCH REPORT

In. stional Application No PCT/RO 01/00004

A. CLASSIF IPC 7	HO1M2/10 HO1M2/02 HO1M2/1	2 H01M2/04				
According to	International Patent Classification (IPC) or to both national classific	cation and IPC				
B. FIELDS						
IPC 7	cumentation searched (classification system followed by classification ${\tt H01M}$	ion sympois)				
D	ion searched other than minimum documentation to the extent that	such documents are included in the fields si	earched			
Documentati	ion searched other man minimum documentation to the extent mat	Such Goodineties are are accused in the roles of				
Electronic da	ata base consulted during the international search (name of data ba	ase and, where practical search terms used)			
EPO-Int	ternal, WPI Data, PAJ					
C. DOCUME	ENTS CONSIDERED TO BE RELEVANT					
Category °	Citation of document, with indication, where appropriate, of the re-	elevant passages	Relevant to claim No.			
			(
Υ	DE 16 96 552 A (VESTER G) 28 October 1971 (1971-10-28) page 1, line 12-19 page 6, line 1 -page 7, line 15 figures		1,2			
Υ	DE 23 25 849 A (OFFERMANN KG ACCUMASCHINENBAU;IST SAURE GMBH) 19 December 1974 (1974-12-19) page 2, line 24-30 page 3, line 18 -page 4, line 8 figures page 3	-/	1			
İ						
l						
ł			(:			
X Further documents are listed in the continuation of box C. X Patent family members are listed in annex.						
° Special ca	ategones of cited documents:	"T" later document published after the inte	rnational filing date			
A document defining the general state of the art which is not considered to be of particular relevance The later document published and in the international manner of priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention						
"E" earlier document but published on or after the international filing date "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone						
L document which may throw doubts on priority claim(s) or involve an inventive step when the document is taken alone which is cited to establish the publication date of another citation or other special reason (as specified) *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the						
O docum	ent referring to an oral disclosure, use, exhibition or	document is combined with one or me ments, such combination being obvio	ore other such docu-			
P docum	*P* document published prior to the international filing date but in the art.					
<u> </u>	actual completion of the international search	Date of mailing of the international sec				
2	20 August 2001	27/08/2001				
Name and	mailing address of the ISA	Authorized officer				
	European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Engl, H				

Form PCT/ISA/210 (second sheet) (July 1992)

1

INTERNATIONAL SEARCH REPORT

Inv. atlenal Application No PCT/RO 01/00004

C (Continuation) COCINENTS CONCIDENTS TO SECURITION		PC1/RO 01/00004			
	Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT				
Category °	Citation of document, with indication, where appropriate, of the relevant passages		Relevant to claim No.		
Y	EP 0 676 818 A (LONGCHAMP DANIEL) 11 October 1995 (1995-10-11) column 1, line 45 -column 2, line 29 figures page 3, line 18 -page 4, line 8 figures		1		
Y	FR 2 766 621 A (BB PLAST) 29 January 1999 (1999-01-29) the whole document		2		
Α	DE 297 12 664 U (VB AUTOBATTERIE GMBH; VOLKSWAGENWERK AG (DE)) 18 September 1997 (1997-09-18) the whole document		1		
A	EP 0 598 220 A (ODENWALD CHEMIE GMBH) 25 May 1994 (1994-05-25) the whole document		1		
A	US 5 278 002 A (HIERS JOHN J) 11 January 1994 (1994-01-11) the whole document		1		
Α	DE 43 34 282 A (AEG ANGLO BATTERIES GERMANY GM) 13 April 1995 (1995-04-13) the whole document		1		

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

1

INTERNATIONAL SEARCH REPORT

information on patent family members

Inv. ational Application No PCT/RO 01/00004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 1696552	Α	28-10-1971	NONE	
DE 2325849	A	19-12-1974	NONE	
EP 0676818	A	11-10-1995	CH 685841 A DE 69510589 D DE 69510589 T DE 676818 T	13-10-1995 12-08-1999 17-02-2000 19-09-1996
FR 2766621	A	29-01-1999	NONE	
DE 29712664	U	18-09-1997	DE 19822181 A ES 2155744 A	21-01-1999 16-05-2001
EP 0598220	A	25-05-1994	DE 9215671 U DE 59301106 D	17-03-1994 18-01-1996
US 5278002	A	11-01-1994	AT 164262 T CA 2144061 A,C DE 69317571 D DE 69317571 T EP 0662253 A JP 8501655 T WO 9407279 A	15-04-1998 31-03-1994 23-04-1998 05-11-1998 12-07-1995 20-02-1996 31-03-1994
DE 4334282	A	13-04-1995	FR 2712120 A GB 2283089 A JP 7226192 A ZA 9407886 A	12-05-1995 26-04-1995 22-08-1995 13-04-1995

Form PCT/ISA/210 (patent family annex) (July 1992)